

PP Solvent 25my ST 601

• DESCRIPTION

Solvent based Natural rubber tape. Carrier BOPP 25mic film suitable for manual carton sealing packaging applications.

• PRODUCT APPLICATION

- Manual carton sealing
- Adhesion on uneven surfaces due to excellent power
- Suitable for all sorts of packaging applications.
- Refrigeration use suitable.
- Temperature resistance after application.

• PRODUCT PROPERTIES

- Moisture compatible after application
- Resistant to temperature changes
- Longevity of application
- Resistance to freezing temperatures



TECHNICAL DATA SHEET

• NOMINAL VALUES

Backing	Biaxially Oriented Polypropylene (BOPP)
Adhesive	Solvent-based, Natural Rubber
Tensile Strength TM 5004 by Afera	130 ± 30 (N/mm ²)
Elongation at Break MD TM 5004 by Afera	140 ± 30 (%)
Adhesion to Steel TM 5001 by Afera	5 ± 1 (N/25mm)
Shear to Steel TM 5012 by Afera	over 300 (h, 25mm x 25mm on stainless steel, 23°C)
Rolling Ball Task PSTC-6 (PSTC)	Under 3 (cm)
Film thickness	25 ± 1(mic)
Film Colors	Transparent <input checked="" type="checkbox"/>
Adhesion Color	Transparent <input checked="" type="checkbox"/> Brown <input type="checkbox"/> White <input type="checkbox"/>

Athens: 68, Varis Avenue, 166 73 Voula, Greece,
Tel.: +30 210 899 5388, Fax exports: + 30 210 899 5386
Factory: 3rd km Pr. rd Skala - Atalanti, 352 00 Atalanti,
Greece, Tel.: +30 223330 23725, Fax exports: + 30 22330
23756
info@atlas-tapes.gr, www.atlas-tapes.gr

EFFECTIVE: April 2014

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.

